




DIN 6888



Chavetas de disco

Woodruff keys
Clavettes disque
Chavetas de disco

Acero C45+C (F-114)

Steel C45+C (F-114)
Acier C45+C (F-114)
Aço C45+C (F-114)

Tolerancia b: h9

b Tolerance: h9
Tolérance b: h9
Tolerância b: h9

Tolerancia h: h12

h Tolerance: h12
Tolérance h: h12
Tolerância h: h12

Resistencia mínima a la tracción: 600 N/mm²

Minimum tensile strenght: 600 N/mm²
Résistance minimum à la rupture: 600 N/mm²
Resistência mínima à tração: 600 N/mm²



También disponibles en stock en acero inoxidable. Consulte con nuestro departamento comercial.

We also have stainless steel available in stock. Contact our sales department.

Également disponible sur stock en inox. Nous consulter.

Também disponíveis em estoque em aço inoxidável. Consulte o nosso departamento comercial.



Otras medidas, longitudes especiales y materiales bajo consulta.

Other dimensions, special lengths and materials available on request.

Autres dimensions, longueurs et matières sur demande.

Outras medidas, comprimentos especiais e materiais, disponíveis sob consulta.



Las longitudes en negrita son las más utilizadas.

Bold numbers represent the most commonly used lengths.

En noir les dimensions les plus utilisées.

Os comprimentos em negrito são os mais utilizados.

Medidas fuera de norma DIN.

Dimensions outside DIN standard.

Dimensions hors norme DIN.

Medidas fora da norma DIN.

Ref.?

ejemplo

example

exemple

exemplo

Ref. = 81 - XX - XX - XX
b h d2

DIN 6888
3x5x13

Ref. = 81-3-5-13

b	1	1,5	2	2,5*	3	4	5	6	7	8	10
h	1,4	2,6	2,6	3,7	• 5	3,7	3,7	5	6,5	7,5	10
d2	4	7	7	10	• 13	10	10	13	16	13	16

* Solo admisible para el sector del automóvil.

* Only acceptable for the automotive industry.

* Valable uniquement pour l'industrie automobile.

* Admissível apenas para o setor do automóvel.



